

CLAIMS

What is claimed is:

1. A product for substantially eliminating existing odors and substantially preventing the
production of new odors in matter, comprising in combination oxide and nitrate.

112, 151
Scope

102

2. The product of claim 1 wherein the oxide is selected from the group consisting of: calcium
oxide; magnesium oxide; and sodium oxide.

103

3. The product of claim 1 wherein the oxide is zinc oxide.

103

4. The product of claim 1 wherein the oxide is iron oxide.

103 ✓

5. The product of claim 1 wherein the oxide is hydrogen peroxide.

102 ✓

6. The product of claim 1 wherein the oxide is selected from the group consisting of
hydroxides, carbonate, bicarbonate, percarbonate and silicate.

102

7. The product of claim 2 wherein the nitrate is selected from the group consisting of: sodium,
potassium, calcium, magnesium, ammonium, and aluminum nitrate.

102

8. The product of claim 6 wherein the nitrate is selected from the group consisting of: sodium,
potassium, calcium, magnesium, ammonium, and aluminum nitrate.

102

9. The product of claim 1 wherein the amount of oxide to nitrate is proportional to the amount
of fresh existing odors to the amount of material producing new odors.

102

10. The product of claim 1 wherein the proportion of the oxide and nitrate ingredients is as
follows: 0.1% to 50% calcium nitrate; 0.1% to 99.9% hydrogen peroxide.

102/103

11. The product of claim 1 wherein the proportion of the oxide and nitrate ingredients is as
follows: 0.1% to 99.9% calcium nitrate; 0.1% to 99.9% zinc oxide.

102/103

12. The product of claim 1 wherein the proportion of the oxide and nitrate ingredients is as

01/24/01

follows: 0.1% to 99.9% calcium nitrate; 0.1% to 99.9% zinc oxide, and further comprises a suspension agent. 103

103
18. The product of claim 1 wherein the proportion of the oxide and nitrate ingredients is as follows: 0.1% to 99.9% calcium nitrate; 0.1% to 99.9% iron oxide. 103

5 19. The product of claim 1 in which the product is a polyurethane paint and comprises at least 0.1% to 70% iron oxide; and polyurethane paint. 103

20. The product of claim 1 in which the product is a polyurethane paint comprising at least 0.1% to 70% zinc oxide; and polyurethane paint. 103

21. The product of claim 1 in which the product is Portland cement comprising at least 0.1% to 50% iron oxide; and Portland cement. 103 TM issue. - check spec.

22. The product of claim 1 wherein the product is plaster and comprises at least 0.1% to 70% iron oxide; and plaster of Paris. 103

23. The product of claim 1 wherein the amount of required oxide is proportional to the amount of existing odors the product is exposed to. 102

15 19. The product of claim 1 wherein the product comprises in proportion to 0.1% to 99.9% zinc oxide, 0.1% to 99.9% calcium nitrate; and further comprises a liquid absorbent material. 103

20. The product of claim 1 wherein the product comprises in proportion 0.1% to 99.9% iron oxide; 0.1% to 99.9% calcium nitrate; and further comprises an inorganic moisture absorbent material. 103

20 21. The product of claim 1 wherein the amount of nitrate is proportional to the amount required to maintain aerobic conditions over the required time period. 102

22. The product of claim 1 for use in a lagoon wherein the nitrate ion is 5 to 200 parts per

million.

29. A method of substantially eliminating existing odors and substantially preventing the production of new odors in matter, comprising applying a product to said matter, which product comprises a combination of oxide and nitrate. 102

5 34. The method of claim 23 wherein the oxide is selected from the group consisting of: calcium oxide; magnesium oxide; and sodium oxide. 103

35. The method of claim 23 wherein the oxide is zinc oxide. 102

36. The method of claim 23 wherein the oxide is iron oxide. 103

37. The method of claim 23 wherein the oxide is hydrogen peroxide. 102

38. The method of claim 23 wherein the oxide is selected from the group consisting of hydroxides, carbonate, bicarbonate, percarbonate and silicate. 102

39. The method of claim 24 wherein the nitrate is selected from the group consisting of: sodium, potassium, calcium, magnesium, ammonium, and aluminum nitrate. 102

40. The method of claim 28 wherein the nitrate is selected from the group consisting of: sodium, potassium, calcium, magnesium, ammonium, and aluminum nitrate. 102

41. The method of claim 23 wherein the amount of oxide to nitrate is proportional to the amount of fresh existing odors to the amount of material producing new odors. 102

32. The method of claim 23 wherein the proportion of the ingredients is as follows: 0.1% to 50% calcium nitrate; 0.1% to 99.9% hydrogen peroxide, and the product is applied as a spray. 103

20 42. The method of claim 23 wherein the proportion of the ingredients is as follows: 0.1% to 99.9% calcium nitrate; 0.1% to 99.9% zinc oxide, and the product is applied as a spray. 103

43. The method of claim 23 wherein the proportion of the ingredients is as follows: 0.1% to 103

99.9% calcium nitrate; 0.1% to 99.9% zinc oxide, and further comprises a suspension agent, and the product is applied as a spray.

25. The method of claim 23 wherein the proportion of the ingredients is as follows: 0.1% to 99.9% calcium nitrate; 0.1% to 99.9% iron oxide, and further comprises a suspension agent. 103

5 36. The method of claim 23 in which the product is a polyurethane paint and comprises at least 0.1% to 70% iron oxide; and polyurethane paint. 103

37. The method of claim 23 in which the product is a polyurethane paint comprising at least 0.1% to 70% zinc oxide; and polyurethane paint. 103

38. The method of claim 23 in which the product is Portland cement comprising at least 0.1% to 50% iron oxide; and Portland cement. 112 - TM - Check spec. 103

39. The method of claim 23 wherein the product is at least comprised of plaster of Paris and 0.1% to 70% zinc oxide. missing the nitrate - not further limiting?

40. The method of claim 23 wherein the product is at least 1 part calcium nitrate and additionally comprises water and the product is applied as a spray.

15 41. The method of claim 23 wherein the product comprises in proportion to grams, 10 grams zinc oxide, 200 grams of calcium nitrate; and additionally, comprises water. 103 } Composition

42. The method of claim 23 wherein the product comprises in proportion to grams, 10 grams zinc oxide, 200 grams of calcium nitrate; and additionally water, plus an additional inorganic moisture absorbent material. added. 103

20 43. The method of claim 23 wherein the nitrate is in a solution not exceeding 50% nitrate. 103

44. The method of claim 23 for use in a lagoon wherein the nitrate ion is 5 to 200 parts per million. use claim - lagoon? 102 sewage